

DM-MD8X8-RPS

8x8 DigitalMedia™ Switcher w/Redundant Power Supply

Crestron® DM® Switchers provide the foundation for a complete DigitalMedia system, delivering an advanced, true high-definition multi-room AV signal routing solution that's extremely flexible and installer-friendly. The DM-MD8X8-RPS affords low-latency switching and pure, lossless distribution of HDMI® and other signals to support the latest Blu-ray Disc® players, HDTV receivers, digital media servers, computers, and all your other AV devices. Integrated Ethernet networking and USB HID distribution provide a complete connectivity solution. And naturally, Crestron control is built in for managing the displays and other room devices without necessitating any additional wiring. The DM-MD8X8-RPS also features built-in redundant power supplies to ensure continuous reliable operation for mission critical applications.

The DM-MD8X8-RPS is field-configurable to handle up to 8 AV sources of virtually any type. The outputs are also field-configurable to provide up to 8 DM room outputs and/or HDMI outputs in a single chassis, with expansion capability possible for up to 40 outputs using multiple chassis. A full selection of DM switcher input cards, DM transmitters, and DM receivers provides extensive connectivity throughout a residence or commercial facility, supporting a complete range of analog and digital signal types — all through one switcher!

DigitalMedia thoughtfully manages all of your disparate AV signals and devices to ensure an optimum video image and audio signal at every location. User-friendly setup and troubleshooting tools are provided through the DM-MD8X8-RPS front panel, or via Crestron Toolbox™ software, to make setting up a complete multi-room HD system easy.

DigitalMedia 8G™

You can't talk about AV and home entertainment today without talking about high-definition, and creating a professional HD AV distribution system means handling the challenges that come with HDMI. HDMI is the standard for interfacing high-definition AV equipment, but despite its many benefits, wasn't developed with multi-room distribution in mind. So, as the leader in HDMI and control system technologies, Crestron developed DigitalMedia, the first complete HD AV distribution system to take HDMI to a higher level, allowing virtually any mix of AV sources to be distributed throughout a room, structure or across a campus from a centralized rack location.

DigitalMedia 8G is the latest generation of DM, providing the world's only truly professional, one-wire digital AV distribution and control network. Engineered for ultra high-bandwidth and ultimate scalability, DM 8G™ handles uncompressed video beyond high-definition with support for HDCP, Deep Color, and 3D, plus high-bitrate 7.1 audio formats including Dolby® TrueHD and DTS-HD Master Audio™, uncompressed multichannel PCM audio, and high-speed Ethernet, all over one 8-conductor twisted-pair wire or simplex multimode fiber. DM 8G enables wire distances up to 330 feet (100 m) via DM 8G+ (DM 8G over CAT5e)^[1,5], or 1000 ft via DM 8G Fiber (DM 8G over simplex multimode fiber)^[2,5], without any need for repeaters.

The DM-MD8X8-RPS provides full support for Crestron DigitalMedia 8G devices as well as all first-generation DM CAT^[3,5] and DM Fiber^[4,5] products, letting you take advantage of the latest Crestron DM technology without compromising your existing investment.

Modular Architecture

The DM-MD8X8-RPS features a modular architecture with 8 input card



slots, and 2 quad output card slots. Each card slot on the DM-MD8X8-RPS is field-installable, allowing for easy and flexible system configuration with the ability to make changes to the system as needs change.

A wide selection of input cards is offered to support a complete range of digital and analog AV signal types including HDMI, DVI, DisplayPort Multimode^[6], SDI, analog video and RGB, SPDIF and analog audio, and DigitalMedia.

One or two output cards may be installed to feed up to 8 DM Receivers/Room Controllers using your choice of DM 8G+, DM 8G Fiber, DM CAT, or DM Fiber. HDMI outputs are also available for direct connection to centralized audio processors and video monitors.

Output Expansion

An HDMI "pass-thru" output is provided on every input card to allow the inputs of up to 5 DM switchers to be daisy-chained, enabling the configuration of very large distribution systems with many DM and HDMI outputs. Using five DM-MD8X8-RPS switchers, it is possible to support an incredible 40 separate outputs.

Computer Compatibility

Besides handling every available HDTV format supported by HDMI, DigitalMedia also supports the distribution of DVI, DisplayPort Multimode^[6], and RGB computer sources, and is fully compatible with DVI computer monitors up to 1920 x 1200 WUXGA.

EDID Format Management

With all of today's varied AV sources comes a multitude of confusing video and audio formats to keep track of, and chances are not every device in your system supports all of the same formats. Such conflicts can wreak havoc any time you route one source to more than one display or audio component. For instance, the Blu-ray player that's feeding your 1080p projector in the theater may restrict itself to a lower resolution, or even shut off completely, if someone decides to view the same signal on the 20" TV in the kitchen. And, instead of enjoying your theater's incredible 7.1 surround sound, you may find yourself limited to 5.1 or even plain old stereo.

DigitalMedia eliminates such conflicts by managing the EDID (Extended

DM-MD8X8-RPS

Display Identification Data) that many devices use to communicate their capabilities. Via Crestron Toolbox software, the format and resolution capabilities of each device can be assessed, allowing the installer to configure EDID signals appropriately for the most desirable and predictable behavior.

A Scaler for Every Display

Scaling capability can be added to any DM system using select DM receivers with built in high-definition scalers.^[7] By placing an independent high-performance scaler at every display device, DigitalMedia truly delivers the most flexible and user-friendly solution for routing multiple disparate sources to many different display devices. This "Distributed Scaler Approach" ensures an optimal image on every screen no matter what sources are selected. Distributed scaling allows a high-res computer source to be viewed on any display in the building, and allows a high-definition 3D source to be viewed on lower-resolution 2D displays without compromising the original signal, letting you share your theater's full HD 1080p 3D image with smaller, lesser displays in the kitchen, bathroom, and bedrooms.

QuickSwitch HD® Technology

Handling high-definition digital media means handling HDCP (High-bandwidth Digital Content Protection), the encryption scheme that content providers use to protect their DVDs, Blu-ray Discs, and broadcast signals against unauthorized copying. Viewing HDCP encrypted content requires a source device to "authenticate" each display and signal processor in the system and issue it a "key" before the content can be viewed. Ordinarily this causes a complete loss of signal for up to 15 seconds each time a new source or display is selected anywhere in the system. To make matters worse, every source device has a limited number of keys available, so connect too many displays and the source will simply stop outputting a signal without warning.

Not to worry — Crestron QuickSwitch HD manages the keys for every HDCP-compliant device in the system, maintaining continuous authentication for each device to ensure fast, reliable routing of any source to any number of display devices.

Versatile Audio Routing

HDMI is the key to handling all the latest 7.1 surround sound formats like Dolby TrueHD and DTS-HD Master Audio. Great for your high-end home theater, but how do you share that same source with other audio zones in the house?

DigitalMedia provides the answer, allowing for the simultaneous distribution of multi-channel surround sound and two-channel stereo signals from the same HDMI source. Using a choice of DSP-based input cards, the DM-MD8X8-RPS employs onboard digital processing to derive a stereo down-mix from the original multi-channel signal. Both signals can be routed separately or simultaneously from any of the switcher's DM outputs, allowing either signal to be selected for output at each DM receiver location.

Back at the switcher, the digital stereo signal is also converted to analog to enable sharing with every other room in the house via a Sonnex™, Adagio®, or other multi-room audio distribution system. The DM-MD8X8-RPS also allows bulky surround sound processors and amplifiers to be located centrally instead of at the display location via optional local HDMI outputs.

Built-in Ethernet Switch

In addition to transporting digital video and audio, DigitalMedia can also extend 10/100 Ethernet out to each display and source device via DM room controllers and select DM transmitters, providing high-speed connectivity for any room device that requires a LAN connection.

USB HID Switch

DigitalMedia lets you centralize ALL of your HD sources - not just television receivers and DVD changers, but also media servers and computers. Built-in USB HID (Human Interface Device) signal routing allows USB HID compatible keyboards and mice to be connected at a remote display location, conference table or presentation lectern, extending their signals through to the centralized equipment via USB HID ports provided on select switcher input cards.

CEC Embedded Device Control

The primary objective of every Crestron system is to enable precisely the control desired for a seamless user experience. DigitalMedia provides an alternative to conventional IR and RS-232 device control by harnessing the CEC (Consumer Electronics Control) signal embedded in HDMI. Through its connection to the control system, the DM-MD8X8-RPS provides a gateway for controlling many devices right through their HDMI connections, potentially eliminating the need for any dedicated control wires or IR probes. Through proper CEC signal management, DigitalMedia allows you to take control of each device as you like.

Easy Setup

Via the front panel or using Crestron Toolbox software, every step of the DM-MD8X8-RPS's setup process is designed to be quick and easy, configuring inputs and outputs automatically while letting the installer make intelligent design decisions along the way. The switcher even tests and measures the length of each DM cable, automatically making the appropriate calibrations for optimal signal transmission to every room. With DigitalMedia, an entire 8x8 system can be commissioned in as little as 15 minutes.

Redundant Power Supplies

The DM-MD8X8-RPS model delivers enhanced reliability for mission critical applications employing extreme long-life, redundant power supplies to ensure continuous dependable operation throughout the life of the system. Each of its internal switch-mode power supplies has a demonstrated MTBF (Mean Time Between Failures) of over 1,000,000 hours, and in the unlikely event of an individual power supply fault, the DM-MD8X8-RPS will continue to operate unhindered on only one power supply. Clear indication of such a fault is provided on the unit's front panel via a flashing red LED, with individual green LEDs also provided to show the status of each individual power supply. The power supplies can even be remotely monitored via Crestron RoomView® software or any control system touch screen.

Please refer to the DigitalMedia Resources Webpage at <http://www.crestron.com/dmresources/> for additional design tools and reference documents.

> Provides lossless HD AV signal routing over twisted-pair wire or fiber

> Integrates video, audio, networking, and control over one wire

> Affords full matrix switching with ultra high 12.5 Gbps backplane data rate

> Handles HDMI® with Deep Color, 3D, and high-bitrate 7.1 encoded audio

> Supports video resolutions up to WUXGA 1920x1200 and HD 1080p60

> Allows up to 330 ft (100 m) wire distance via DM 8G+™^[1,5]

DM-MD8X8-RPS

- > QuickSwitch HD® technology manages HDCP keys for reliable, low-latency switching
- > Detects and displays detailed video and audio input information
- > Performs automatic AV signal format management via EDID
- > Allows independent scaling for every display through select DM receivers¹⁷
- > Enables device control via CEC
- > Distributes USB HID mouse and keyboard signals
- > Allows full audio and USB breakaway switching
- > Integrates with analog audio distribution systems
- > Enables simultaneous output of stereo and surround sound audio
- > Includes integrated Ethernet switch with Gigabit LAN port
- > Includes built-in power distribution for DM transmitters, repeaters, and room controllers⁸¹
- > Built-in redundant power supplies with remote status monitoring
- > Provides easy setup and diagnostics tools via front panel or software
- > 4-space 19-inch rack-mountable

SPECIFICATIONS

Video

Switcher: 8x8 digital matrix, modular input/output cards, Crestron QuickSwitch HD®

Input Signal Types: Configurable via modular plug-in cards supporting HDMI®, DisplayPort Multimode⁶¹, DVI, SDI, RGB, component (YPbPr), S-Video (Y/C), composite video, DM CAT, DM Fiber, DM 8G+, and DM 8G Fiber

Output Signal Types: Configurable via modular plug-in cards supporting DM CAT, DM Fiber, DM 8G+, DM 8G Fiber, HDMI, and DVI⁹¹ (All input cards also include HDMI pass-thru outputs)

Formats: HDMI w/Deep Color & 3D, DVI, HDCP content protection support, SD-SDI, HD-SDI, 3G-SDI, RGBHV up to UXGA/WUXGA, HDTV up to 1080p60, NTSC or PAL

Input Resolutions, HDMI & DVI, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

Input Resolutions, HDMI & DVI, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

Input Resolutions, RGB: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 1024x768@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz,

Audio

Switcher: 8x8 digital multi-channel audio-follow-video matrix switching, plus independent 8x8 stereo matrix for audio breakaway

Input Signal Types: Configurable via modular plug-in cards supporting HDMI, DisplayPort Multimode⁶¹, SDI, analog (stereo 2-channel), SPDIF, DM CAT, DM Fiber, DM 8G+, and DM 8G Fiber

Output Signal Types: Configurable via modular plug-in cards supporting DM CAT, DM Fiber, DM 8G+, DM 8G Fiber, HDMI, and analog (stereo 2-channel); (All input cards also include HDMI pass-thru outputs, and most digital audio input cards also include analog stereo pass-thru audio outputs)

Formats, HDMI only: Dolby Digital® Plus, Dolby® TrueHD, DTS-HD High Res, DTS-HD Master Audio™, up to 8ch PCM

Formats, HDMI and SPDIF: Dolby Digital, Dolby Digital EX, DTS®, DTS-ES, DTS 96/24, 2ch PCM

Formats, Analog: Stereo 2-Channel

Formats, SDI: (see DMC-SDI spec sheet)

Communications

DigitalMedia: DM Fiber, DM CAT, DMNet®, DM 8G+, DM 8G Fiber, HDCP management, EDID format management, CEC

Ethernet: 10/100/1000 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, TCP/IP, UDP/IP, CIP, DHCP, RSTP

USB: Supports USB HID class devices

Ethernet Switch

Provides (1) onboard 10/100/1000BaseT Gigabit Ethernet port, (1) internal 10BaseT/100BaseTX Ethernet port for the switcher, and (16) remote 10BaseT/100BaseTX Ethernet ports via select outboard devices

USB Switch

8x8 matrix

Card Slots

1 - 8: (8) DM switcher input card slots;

Each slot accepts (1) DMC-series input card

DM OUTPUTS (SLOT 1 - 2): (2) DM switcher output card slots;

Each slot accepts (1) DMCO-series output card

Connectors

LAN: (1) 8-wire RJ45 female;

10/100/1000BaseT Ethernet port

24ABG / EIG 1 - 4 (SLOT 1 - 2): (8) sets of (1) 4-pin and (1) 3-pin 3.5mm detachable terminal blocks;

Comprises (8) DMNet ports with "EIG" power selection ports, each set associated with a corresponding DM CAT output port on the output card in either output slot;

Each DMNet port provides power and communications for a DM CAT device connected via DM cable;

Each EIG port connects to an external power supply⁸¹ to power the DM CAT device connected to the corresponding DMNet port;

Maximum Load: 75 Watts (3.13 Amps @ 24 Volts DC) per port, limited to available DMNet power from external power supply⁸¹

100-240V~225W 50/60Hz: (1) IEC C14 male chassis plug, main power input;

Mates with removable power cord, included

G: (1) 6-32 screw, chassis ground lug

COMPUTER (front): (1) USB Type B female;

USB 1.1 computer console port (6 ft cable included)

LCD Display

Green LCD dot matrix, 128 x 64 resolution, adjustable LED backlight;

Displays inputs/outputs by name, video & audio signal information, Ethernet configuration and setup menus

DM-MD8X8-RPS

Controls & Indicators

SOFTKEYS: (4) pushbuttons for activation of LCD driven functions

HW-R: (1) recessed miniature pushbutton for hardware reset, reboots the switcher

ROUTE: (1) pushbutton and red LED, selects ROUTE mode to allow routing changes

VIEW: (1) pushbutton and red LED, selects VIEW mode for viewing current routes

INFO: (1) pushbutton and red LED, selects INFO mode for viewing AV and device info

MENU: (1) pushbutton, steps menu back one level

ENTER: (1) pushbutton, executes highlighted menu or value

AUDIO: (1) pushbutton & red LED, selects audio routing view

VIDEO: (1) pushbutton & red LED, selects video routing view

USB: (1) pushbutton & red LED, selects USB routing view

Quick-Adjust Knob: (1) continuous turn rotary encoder, adjusts menu parameters

IN 1 - 8: (8) pushbuttons and red LEDs, select input for routing

OUT 1 - 8: (8) pushbuttons and red LEDs, select output for routing

POWER SUPPLIES, 1 - 2: (2) green LEDs, indicate when each corresponding internal supply is functioning

POWER SUPPLIES, FAULT: (1) red flashing LED, indicates a fault with either internal supply

LAN (rear): (2) LEDs, green LED indicates Ethernet link status, amber LED indicates Ethernet activity

Power Requirements

Main Power: 225 Watts @ 100-240 Volts AC, 50/60 Hz

Available DMNet Power: none

Redundant Power Supplies

Quantity/Type: (2) switch-mode, internal

Demonstrated MTBF: >1,000,000 hours per power supply @ full load and 25°C ambient conditions

Redundancy: Complete unit continues to operate at full capacity on one or more functioning power supplies

Environmental

Temperature: 32° to 104°F (0° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 750 BTU/Hr

Enclosure

Chassis: Metal with black finish, vented sides, fan-cooled

Faceplate: Extruded aluminum, black finish with polycarbonate label overlay

Mounting: Freestanding or 4U 19-inch rack-mountable (adhesive feet and rack ears included)

Dimensions

Height: 6.97 in (177 mm) without feet

Width: 17.28 in (439 mm), 19.00 in (483 mm) with ears

Depth: 15.70 in (399 mm) without cards

Weight

20.0 lb (9.1 kg) without cards

Available Models

DM-MD8X8-RPS: 8x8 DigitalMedia™ Switcher w/Redundant Power Supply

Available Accessories

DMC-HD: HDMI® Input Card

DMC-HD-DSP: HDMI® Input Card w/Down-mixing

DMC-DVI: DVI/RGB Input Card

DMC-VID-RCA-A: RCA Analog Video Input Card w/Analog Audio

DMC-VID-RCA-D: RCA Analog Video Input Card w/SPDIF Audio

DMC-VID-BNC: BNC Analog Video Input Card

DMC-VID4: Quad Video Input Card

DMC-SDI: SDI Input Card

DMC-CAT: DigitalMedia™ CAT Input Card

DMC-CAT-DSP: DigitalMedia™ CAT Input Card w/Down-mixing

DMC-F: DigitalMedia™ Fiber Input Card

DMC-F-DSP: DigitalMedia™ Fiber Input Card w/Down-mixing

DMC-C: DigitalMedia 8G+™ Input Card

DMC-C-DSP: DigitalMedia 8G+™ Input Card w/Down-mixing

DMC-S: DigitalMedia 8G™ Fiber Input Card

DMC-S-DSP: DigitalMedia 8G™ Fiber Input Card w/Down-mixing

DMCO-10: 2 DM Fiber Output Card

DMCO-11: 4 DM Fiber Output Card

DMCO-20: 2 DM CAT w/1 HDMI Output Card

DMCO-22: 4 DM CAT w/2 HDMI Output Card

DMCO-40: 2 DM 8G Fiber w/1 HDMI Output Card

DMCO-44: 4 DM 8G Fiber w/2 HDMI Output Card

DMCO-50: 2 DM 8G+ w/1 HDMI Output Card

DMCO-55: 4 DM 8G+ w/2 HDMI Output Card

DMCO-30: 2 HDMI w/2 Stereo Analog Audio Output Card

DMCO-33: 4 HDMI w/4 Stereo Analog Audio Output Card

DMCO-12: 2 DM Fiber & 2 DM CAT w/1 HDMI Output Card

DMCO-15: 2 DM Fiber & 2 DM 8G+ w/1 HDMI Output Card

DMCO-13: 2 DM Fiber & 2 HDMI w/2 Stereo Analog Audio Output Card

DMCO-23: 2 DM CAT w/1 HDMI & 2 HDMI w/2 Stereo Analog Audio Output Card

DMCO-45: 2 DM 8G Fiber w/1 HDMI & 2 DM 8G+ w/1 HDMI Output Card

DMCO-43: 2 DM 8G Fiber w/1 HDMI & 2 HDMI w/2 Stereo Analog Audio Output Card

DMCO-53: 2 DM 8G+ w/1 HDMI & 2 HDMI w/2 Stereo Analog Audio Output Card

DM-CBL-NP-SP500: DigitalMedia™ Cable, non-plenum, 500 ft spool

DM-CBL-P-SP500: DigitalMedia™ Cable, plenum-rated, 500 ft spool

DM-CBL-D-NP-SP500: DigitalMedia™ D Cable, non-plenum, 500 ft spool

DM-CBL-D-P-SP500: DigitalMedia™ D Cable, plenum, 500 ft spool

DM-CONN-20: DigitalMedia™ Cable Connectors, 20-Pack

DM-DR: DigitalMedia™ Repeater

DM-CBL-8G-NP-SP500: DigitalMedia 8G™ Cable, non-plenum, 500 ft spool

DM-CBL-8G-P-SP500: DigitalMedia 8G™ Cable, plenum, 500 ft spool

DM-8G-CONN-100: DigitalMedia 8G™ Cable Connector, 100-Pack

CRESFIBER8G-NP-SP500: CresFiber® 8G Fiber Optic Cable, 50/125 x4

breakout, non-plenum, 500 ft spool

CRESFIBER8G-NP-SP1000: CresFiber® 8G Fiber Optic Cable, 50/125 x4

breakout, non-plenum, 1000 ft spool

CRESFIBER8G-P-SP500: CresFiber® 8G Fiber Optic Cable, 50/125 x4

breakout, plenum, 500 ft spool

CRESFIBER8G-P-SP1000: CresFiber® 8G Fiber Optic Cable, 50/125 x4

breakout, plenum, 1000 ft spool

CRESFIBER-CONN-SC50UM-12: CresFiber® Fiber Optic Cable Connector

(AFL Telecommunications™), SC 50µm, 12-Pack

CRESFIBER-DUAL-SC-P-1.5: CresFiber® Duplex Fiber Optic Cable Assembly,

50/125, SC, Plenum, 1.5 ft

CRESFIBER-DUAL-SC-P-3: CresFiber® Duplex Fiber Optic Cable Assembly,

50/125, SC, Plenum, 3 ft

CRESFIBER-DUAL-SC-P-6: CresFiber® Duplex Fiber Optic Cable Assembly,

50/125, SC, Plenum, 6 ft

CRESFIBER-DUAL-SC-P-12: CresFiber® Duplex Fiber Optic Cable Assembly,

50/125, SC, Plenum, 12 ft

CRESFIBER-DUAL-SC-P-20: CresFiber® Duplex Fiber Optic Cable Assembly,

50/125, SC, Plenum, 20 ft

DM-MD8X8-RPS

CRESFIBER-SINGLE-SC-ARMORED-P-100: CresFiber® ARMORED Simplex Fiber Optic Cable Assembly, 50/125, SC, Armored, Plenum, 100 ft
CRESFIBER-SINGLE-SC-ARMORED-P-200: CresFiber® ARMORED Simplex Fiber Optic Cable Assembly, 50/125, SC, Armored, Plenum, 200 ft
CRESFIBER-SINGLE-SC-ARMORED-P-300: CresFiber® ARMORED Simplex Fiber Optic Cable Assembly, 50/125, SC, Armored, Plenum, 300 ft
CRESFIBER-SINGLE-SC-CLEAR-NP-30: CresFiber® CLEAR Simplex Fiber Optic Cable Assembly, 50/125, SC, Non-Plenum, 30 ft
CRESFIBER-SINGLE-SC-CLEAR-NP-60: CresFiber® CLEAR Simplex Fiber Optic Cable Assembly, 50/125, SC, Non-Plenum, 60 ft
CRESFIBER-SINGLE-SC-CLEAR-NP-100: CresFiber® CLEAR Simplex Fiber Optic Cable Assembly, 50/125, SC, Non-Plenum, 100 ft

Notes:

1. The maximum DigitalMedia 8G+ cable length is 330 ft (100 m) using DM-CBL-8G DigitalMedia 8G cable, DM-CBL DigitalMedia Cable, DM-CBL-D DigitalMedia D Cable, or generic CAT5e (or better) UTP or STP. Shielded cable and connectors are recommended to safeguard against unpredictable environmental electrical noise which may impact performance at resolutions above 1080p.
2. The maximum DigitalMedia 8G Fiber cable length is 1000 ft (300 m) using CRESFIBER8G fiber optic cable, or 500 ft (150 m) using standard CRESFIBER, CRESFIBER-SINGLE-SC, or generic OM3 simplex multimode fiber optic cable.
3. The maximum DigitalMedia CAT cable length is 450 ft (137 m) using DM-CBL DigitalMedia Cable. Actual cable length depends upon multiple factors. Up to two DM Repeaters (Model DM-DR) may be required.
4. The maximum DigitalMedia Fiber cable length is 1000 ft (300 m) using CRESFIBER, CRESFIBER8G, CRESFIBER-DUAL-SC, or generic OM2/OM3 duplex multimode fiber optic cable.
5. Refer to the DigitalMedia Infrastructure Guide, Doc. #4556 for complete wiring guidelines, and the Crestron DigitalMedia Design Guide, Doc. #4789 for complete system design guidelines. All cable sold separately.
6. DisplayPort Multimode connectivity is supported via an HDMI or DVI input port using a suitable adapter or interface cable.
7. DM receivers with built-in scaling include the DM-RMC-SCALER-C and DM-RMC-200-C. All DM receivers sold separately.
8. External power supply required, sold separately. For external DMNet power, use a Crestron CNPWS-75, C2N-SPWS300, or other Cresnet power supply as required. Do not interconnect DMNet with Cresnet.
9. DVI output is supported via an HDMI output port using a suitable adapter or interface cable. CBL-HD-DVI interface cable available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

Crestron, the Crestron logo, Adagio, CresFiber, Crestron Toolbox, DigitalMedia, DigitalMedia 8G, DigitalMedia 8G+, DM, DM 8G, DM 8G+, DMNet, QuickSwitch HD, and Sonnex are trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and other countries. Blu-ray Disc is either a trademark or registered trademark of the Blu-ray Disc Association in the United States and/or other countries. Dolby, Dolby Digital, and the double-D symbol are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD Master Audio, and is a registered trademark & the DTS logos and Symbol are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI, and the HDMI Logo, and High-Definition Multimedia Interface are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims proprietary interest in the marks and names of others. ©2011 Crestron Electronics, Inc.

DM-MD8X8-RPS

